



PLEASE READ IMMEDIATELY

DO NOT ATTEMPT TO POWER-ON OR OPERATE VEHICLE BEFORE READING THIS NOTICE

**Your MAMBA-25 ESC requires calibration to your
Transmitter prior to any type of operation.**

**Failure to follow these steps can result in bodily harm and/or
damage to your vehicle.**

Follow these steps:

1. Place batteries in the Transmitter as outlined in your PHOTON instruction manual.
2. Fully charge the vehicles LiPo battery that was supplied with your PHOTON as outlined in your PHOTON manual.
3. Go directly to the MAMBA-25 ESC instruction manual that was supplied with your PHOTON and read the entire set of instructions in order to become familiar with the MAMBA-25. ***DO NOT SET REVERSE ANY HIGHER THAN 50%.** It will not be necessary to perform steps 1.0 through 2.3 in the MAMBA-25 instructions because these steps have already been performed at our factory. The battery supplied with your vehicle is a 3 Cell 11.1volt Li-Po. Go to step 3.0 "Communicating with your new Mamba-25" and continue performing the Mamba-25 instructions until completed.
4. **IMPORTANT**** Because your vehicle battery is a Li-Po, you must change the default cut-off voltage BEFORE running your vehicle. Make sure you have performed this step in the Mamba-25 instructions.
5. Now return to the PHOTON manual and follow the instructions for checking and operating your new PHOTON.

**Please contact the dealer from whom you have purchased
this product if you have any questions. Thank you.**

